

K10.205 Clause for Spacetherm P

K10 PLASTERBOARD DRY LININGS/PARTITIONS/CEILINGS

205 LINING ON TIMBER

Comprises a Spacetherm insulation blanket laminated to a plywood reinforced plasterboard.

Application: Allows easy upgrading of existing properties with the minimum loss of internal space.

Insulation thickness: 3mm, 6mm, 9mm

Plasterboard thickness: 10mm, 12.5mm, 15mm, 18mm

Thermal conductivity: 0.013W/mK

Installation:

Mechanically fixed using fixings appropriate to the substrate.

Panel joints taped and filled.

Further Information

Additional information and literature may be available from A Proctor Group Ltd., The Haugh, Blairgowrie, Perthshire, PH10 7ER. Tel: 01250 872261. Fax: 01250 872727. Email: technical@proctorgroup.com. Website: www.proctorgroup.com.

K10.225 Clause for Spacetherm P

K10 PLASTERBOARD DRY LININGS/PARTITIONS/CEILINGS

225 SUSPENDED CEILING SYSTEM (DOUBLE GRID)

Comprises a Spacetherm insulation blanket laminated to a plywood reinforced plasterboard.

Application: Allows easy upgrading of existing properties with the minimum loss of internal space.

Insulation thickness: 3mm, 6mm, 9mm

Plasterboard thickness: 10mm, 12.5mm, 15mm, 18mm

Thermal conductivity: 0.013W/mK

Installation:

Mechanically fixed using fixings appropriate to the substrate.

Panel joints taped and filled.

Further Information

Additional information and literature may be available from A Proctor Group Ltd., The Haugh, Blairgowrie, Perthshire, PH10 7ER. Tel: 01250 872261. Fax: 01250 872727. Email: technical@proctorgroup.com. Website: www.proctorgroup.com.

K10.235 Clause for Spacetherm P

K10 PLASTERBOARD DRY LININGS/PARTITIONS/CEILINGS

235 SUSPENDED CEILING SYSTEM (SINGLE GRID)

Comprises a Spacetherm insulation blanket laminated to a plywood reinforced plasterboard.

Application: Allows easy upgrading of existing properties with the minimum loss of internal space.

Insulation thickness: 3mm, 6mm, 9mm

Plasterboard thickness: 10mm, 12.5mm, 15mm, 18mm

Thermal conductivity: 0.013W/mK

Installation:

Mechanically fixed using fixings appropriate to the substrate.

Panel joints taped and filled.

Further Information

Additional information and literature may be available from A Proctor Group Ltd., The Haugh, Blairgowrie, Perthshire, PH10 7ER. Tel: 01250 872261. Fax: 01250 872727. Email: technical@proctorgroup.com. Website: www.proctorgroup.com.

K10.245 Clause for Spacetherm P

K10 PLASTERBOARD DRY LININGS/PARTITIONS/CEILINGS

245 CEILING LINING ON TIMBER

Comprises a Spacetherm insulation blanket laminated to a plywood reinforced plasterboard.

Application: Allows easy upgrading of existing properties with the minimum loss of internal space.

Insulation thickness: 3mm, 6mm, 9mm

Plasterboard thickness: 10mm, 12.5mm, 15mm, 18mm

Thermal conductivity: 0.013W/mK

Installation:

Mechanically fixed using fixings appropriate to the substrate.

Panel joints taped and filled.

Further Information

Additional information and literature may be available from A Proctor Group Ltd., The Haugh, Blairgowrie, Perthshire, PH10 7ER. Tel: 01250 872261. Fax: 01250 872727. Email: technical@proctorgroup.com. Website: www.proctorgroup.com.